Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1-43. (Canceled)

44. (Previously Presented) A tissue ablation device for ablating a circumferential region of tissue associated with an orifice of a vein that carries blood to an atrium, comprising:

a member adapted to be positioned adjacent to the circumferential region of tissue; and

an ablation element associated with the member and adapted to form a lesion in a substantial portion of the circumferential region of tissue.

- 45. (Previously Presented) A tissue ablation device as claimed in claim 44, wherein the member defines a size and shape corresponding to the circumferential region of tissue.
- 46. (Previously Presented) A tissue ablation device as claimed in claim 45, wherein the size and shape is adapted to engage the tissue surrounding one of a superior vena cava, an inferior vena cava and a pulmonary vein.
- 47. (Previously Presented) A tissue ablation device as claimed in claim 44, wherein the member comprises a collapsible member.
- 48. (Previously Presented) A tissue ablation device as claimed in claim 47, wherein the collapsible member comprises a collapsible loop structure.

- 49. (Previously Presented) A tissue ablation device as claimed in claim 44, wherein the ablation element comprises an energy emitting structure.
- 50. (Previously Presented) A tissue ablation device as claimed in claim 49, wherein the ablation element comprises a plurality of spaced energy emitting elements.
- 51. (Previously Presented) A tissue ablation device for ablating a substantial portion of a circumferential region of tissue where a pulmonary vein extends from an atrium, comprising:

an elongate body with a distal end portion and a proximal end portion;

an expandable member coupled to the elongate body adjustable between a radially collapsed condition and a radially expanded condition with an expanded outer diameter which is adapted to engage the substantial portion of the circumferential region of tissue;

an ablation element associated with the expandable member and adapted to emit a substantially circumferential pattern of energy and to ablatively couple to the substantial portion of the circumferential region of tissue engaged by the expandable member in the radially expanded condition when the ablation element is coupled to and actuated by an ablation actuator.

52. (Previously Presented) A tissue ablation device for ablating a substantial portion of a circumferential region of tissue where a vein extends from an atrium, comprising:

an elongate body with a distal end portion and a proximal end portion;

an expandable member coupled to the elongate body adjustable between a radially collapsed condition and a radially expanded condition with an expanded outer diameter which is adapted to engage the substantial portion of the circumferential region of tissue; an ablation element associated with the expandable member and adapted to emit a substantially circumferential pattern of energy and to ablatively couple to the substantial portion of the circumferential region of tissue engaged by the expandable member in the radially expanded condition when the ablation element is coupled to and actuated by an ablation actuator.

53. (Previously Presented) A tissue ablation system for treating atrial arrhythmia in a patient, comprising:

a circumferential ablation member which is adapted to be delivered to a position relative to a circumferential region of tissue at a location where a pulmonary vein extends from an atrium in the patient, the circumferential ablation member having an ablation element which is adapted to ablate a substantial portion of the circumferential region of tissue without delivery of an ablative fluid to the tissue.

- 54. (Previously Presented) The system of claim 53, wherein the ablation element comprises a light emitting ablation element.
- 55. (Previously Presented) The system of claim 53, wherein the ablation element comprises a tissue cooling ablation element.
- 56. (Previously Presented) The system of claim 53, wherein the ablation element comprises a microwave ablation element.
- 57. (Previously Presented) The system of claim 53, wherein the ablation element comprises a thermal ablation element.
- 58. (Previously Presented) The system of claim 53, wherein the ablation element is adapted to be coupled to and actuated by an ablation actuator.

- 59. (Previously Presented) The system of claim 53, further comprising an elongate body with a proximal end portion and a distal end portion, wherein the circumferential ablation member is located at least in part along the distal end portion, and the elongate body is adapted to deliver the circumferential ablation member to the desired position.
- 60. (Previously Presented) The system of claim 53, further comprising a delivery system cooperating with the circumferential ablation member and which is adapted to deliver the circumferential ablation member to the desired position.
- 61. (Previously Presented) The system of claim 53, wherein the ablation element is adapted to ablate a substantial portion of the circumferential region of tissue without delivery of electrical current.
- 62. (Previously Presented) A tissue ablation system for treating atrial arrhythmia in a patient, comprising:
- a circumferential ablation member which is adapted to be delivered to a position relative to a circumferential region of tissue at a location where a vein extends from an atrium in the patient, the circumferential ablation member having an ablation element which is adapted to ablate a substantial portion of the circumferential region of tissue without delivery of an ablative fluid to the tissue.
- 63. (Previously Presented) The system of claim 62, wherein the ablation element comprises a light emitting ablation element.
- 64. (Previously Presented) The system of claim 62, wherein the ablation element comprises a tissue cooling ablation element.
- 65. (Previously Presented) The system of claim 62, wherein the ablation element comprises a microwave ablation element.

- 66. (Previously Presented) The system of claim 62, wherein the ablation element comprises a thermal ablation element.
- 67. (Previously Presented) The system of claim 62, wherein the ablation element is adapted to be coupled to and actuated by an ablation actuator.
- 68. (Previously Presented) The system of claim 62, further comprising an elongate body with a proximal end portion and a distal end portion, wherein the circumferential ablation member is located at least in part along the distal end portion, and the elongate body is adapted to deliver the circumferential ablation member to the desired position.
- 69. (Previously Presented) The system of claim 62, further comprising a delivery system cooperating with the circumferential ablation member and which is adapted to deliver the circumferential ablation member to the desired position.
- 70. (Previously Presented) The system of claim 62, wherein the ablation element is adapted to ablate a substantial portion of the circumferential region of tissue without delivery of electrical current.
- 71. (Previously Presented) A tissue ablation device system for ablating a circumferential region of tissue at a location where a single pulmonary vein extends from an atrium in a patient, comprising:

an ablation member with a contact member which is adapted to substantially contact the circumferential region of tissue, and also with an ablation element which is adapted to be ablatively coupled to the circumferential region of tissue when the circumferential ablation member is positioned at the location; and

a delivery assembly that cooperates with the circumferential ablation member and that is adapted to deliver the circumferential ablation member to the location.

- 72. (Previously Presented) The tissue ablation device system of claim 71, wherein the contact member comprises a body that is adapted to have a looped geometry which substantially contacts the circumferential region of tissue.
- 73. (Previously Presented) The tissue ablation device system of claim 72, wherein

the contact member is adapted to be positioned in a collapsed geometry within a delivery passageway of a delivery catheter and to be delivered through the delivery passageway and into the atrium; and

the contact member is adjustable to the looped geometry when the contact member is positioned externally of the delivery passageway.

- 74. (Previously Presented) The tissue ablation device system of claim 72, wherein the looped geometry is sized to engage the pulmonary vein.
- 75. (Previously Presented) The tissue ablation device system of claim 71, wherein the contact member is adjustable from a first configuration, which is adapted to be delivered through a delivery passageway of a delivery catheter and into the atrium, to a second configuration which is adapted to contact the circumferential region of tissue.
- 76. (Previously Presented) The tissue ablation device system of claim 71, wherein

the delivery assembly comprises a delivery catheter with a proximal end portion and a distal end portion and a delivery passageway extending between a distal

port along the distal end portion and a proximal port located proximally of the distal port; and

the ablation member is adapted to be advanced through the delivery passageway and into the atrium through the distal port.

77. (Previously Presented) The tissue ablation device system of claim 71, wherein the delivery assembly comprises an elongate body with a proximal end portion and a distal end portion; and

the ablation member is located at least in part along the distal end portion of the elongate body.

- 78. (Previously Presented) The tissue ablation device system of claim 77, wherein the contact member is located at least in part along the distal end portion of the elongate body.
- 79. (Previously Presented) The tissue ablation device system of claim 71, wherein the ablation element comprises at least one electrode that is adapted to couple to an electrical current source.
- 80. (Previously Presented) The tissue ablation device system of claim 71, wherein the ablation element comprises a plurality of electrodes that are located at least in part along the contact member and that are adapted to couple to an electrical current source.
- 81. (Previously Presented) The tissue ablation device system of claim 71, wherein the ablation element comprises a cooling ablation element.
- 82. (Previously Presented) The tissue ablation device system of claim 71, wherein the ablation element comprises a light emitting ablation element.

- 83. (Previously Presented) The tissue ablation device system of claim 71, wherein the ablation element comprises a microwave ablation element.
- 84. (Previously Presented) The tissue ablation device system of claim 71, wherein the ablation element comprises a thermal ablation element.
- 85. (Previously Presented) The tissue ablation device system of claim 71, wherein the ablation element comprises a chemical fluid ablation element.
- 86. (Previously Presented) A tissue ablation device system for ablating a circumferential region of tissue at a location where a pulmonary vein extends from an atrium, comprising:
- a circumferential ablation member with an ablation element which is adapted to ablatively couple to the circumferential region of tissue when the circumferential ablation member is positioned along the location; and
- a delivery member with a proximal end portion and a distal end portion, wherein the circumferential ablation member is located at least in part along the distal end portion and is adapted to be delivered to the location at least in part with the delivery member,

wherein the system is adapted to allow a volume of blood to flow from the pulmonary vein, across the location, and into the atrium when the circumferential ablation member is positioned along the location and the ablation element is ablatively coupled to the circumferential region of tissue.

87. (Previously Presented) The tissue ablation device assembly as in claim 86, wherein the circumferential ablation member additionally includes an expandable member cooperating with the ablation element and which is adapted to substantially engage the circumferential region of tissue when the ablation element is ablatively coupled to the circumferential region of tissue.

- 88. (Previously Presented) The tissue ablation device assembly of claim 86, wherein the ablation element further comprises an electrode ablation element.
- 89. (Previously Presented) The tissue ablation device assembly of claim 86, wherein the ablation element further comprises a thermal ablation element.
- 90. (Previously Presented) The tissue ablation device assembly of claim 86, wherein the ablation element further comprises a light emitting ablation element.
- 91. (Previously Presented) The tissue ablation device assembly of claim 86, wherein the ablation element further comprises a microwave ablation element.
- 92. (Previously Presented) The tissue ablation device assembly of claim 86, wherein the ablation element further comprises a chemical ablation element.
- 93. (Previously Presented) A tissue ablation device system for ablating a circumferential region of tissue at a location where a single vein extends from an atrium in a patient, comprising:
- an ablation member with a contact member which is adapted to substantially contact the circumferential region of tissue, and also with an ablation element which is adapted to be ablatively coupled to the circumferential region of tissue when the circumferential ablation member is positioned at the location; and
- a delivery assembly that cooperates with the circumferential ablation member and that is adapted to deliver the circumferential ablation member to the location.
- 94. (Previously Presented) The tissue ablation device system of claim 93, wherein the contact member comprises a body that is adapted to have a looped geometry which substantially contacts the circumferential region of tissue.

95. (Previously Presented) The tissue ablation device system of claim 94, wherein

the contact member is adapted to be positioned in a collapsed geometry within a delivery passageway of a delivery catheter and to be delivered through the delivery passageway and into the atrium; and

the contact member is adjustable to the looped geometry when the contact member is positioned externally of the delivery passageway.

- 96. (Previously Presented) The tissue ablation device system of claim 94, wherein the looped geometry is sized to engage the vein.
- 97. (Previously Presented) The tissue ablation device system of claim 93, wherein the contact member is adjustable from a first configuration, which is adapted to be delivered through a delivery passageway of a delivery catheter and into the atrium, to a second configuration which is adapted to contact the circumferential region of tissue.
- 98. (Previously Presented) The tissue ablation device system of claim 93, wherein

the delivery assembly comprises a delivery catheter with a proximal end portion and a distal end portion and a delivery passageway extending between a distal port along the distal end portion and a proximal port located proximally of the distal port; and

the ablation member is adapted to be advanced through the delivery passageway and into the atrium through the distal port.

99. (Previously Presented) The tissue ablation device system of claim 93, wherein the delivery assembly comprises an elongate body with a proximal end portion and a distal end portion; and

the ablation member is located at least in part along the distal end portion of the elongate body.

- 100. (Previously Presented) The tissue ablation device system of claim 99, wherein the contact member is located at least in part along the distal end portion of the elongate body.
- 101. (Previously Presented) The tissue ablation device system of claim 93, wherein the ablation element comprises at least one electrode that is adapted to couple to an electrical current source.
- 102. (Previously Presented) The tissue ablation device system of claim 93, wherein the ablation element comprises a plurality of electrodes that are located at least in part along the contact member and that are adapted to couple to an electrical current source.
- 103. (Previously Presented) The tissue ablation device system of claim 93, wherein the ablation element comprises a cooling ablation element.
- 104. (Previously Presented) The tissue ablation device system of claim 93, wherein the ablation element comprises a light emitting ablation element.
- 105. (Previously Presented) The tissue ablation device system of claim 93, wherein the ablation element comprises a microwave ablation element.
- 106. (Previously Presented) The tissue ablation device system of claim 93, wherein the ablation element comprises a thermal ablation element.
- 107. (Previously Presented) The tissue ablation device system of claim 93, wherein the ablation element comprises a chemical fluid ablation element.

- 108. (Previously Presented) A tissue ablation device system for ablating a circumferential region of tissue at a location where a vein extends from an atrium, comprising:
- a circumferential ablation member with an ablation element which is adapted to ablatively couple to the circumferential region of tissue when the circumferential ablation member is positioned along the location; and

a delivery member with a proximal end portion and a distal end portion, wherein the circumferential ablation member is located at least in part along the distal end portion and is adapted to be delivered to the location at least in part with the delivery member,

wherein the system is adapted to allow a volume of blood to flow from the vein, across the location, and into the atrium when the circumferential ablation member is positioned along the location and the ablation element is ablatively coupled to the circumferential region of tissue.

- 109. (Previously Presented) The tissue ablation device assembly as in claim 108, wherein the circumferential ablation member additionally includes an expandable member cooperating with the ablation element and which is adapted to substantially engage the circumferential region of tissue when the ablation element is ablatively coupled to the circumferential region of tissue.
- 110. (Previously Presented) The tissue ablation device assembly of claim 108, wherein the ablation element further comprises an electrode ablation element.
- 111. (Previously Presented) The tissue ablation device assembly of claim 108, wherein the ablation element further comprises a thermal ablation element.
- 112. (Previously Presented) The tissue ablation device assembly of claim 108, wherein the ablation element further comprises a light emitting ablation element.

- 113. (Previously Presented) The tissue ablation device assembly of claim 108, wherein the ablation element further comprises a microwave ablation element.
- 114. (Previously Presented) The tissue ablation device assembly of claim 108, wherein the ablation element further comprises a chemical ablation element.

115-147. (Canceled)